Citrix Access Gateway

Specifications sheet

Citrix® Access Gateway™: Physical appliances		
Model	Model 2010[1]	MPX 5500[2]
Performance		
Max Concurrent Users	500	5000
Physical dimensions		
Form Factor	1 RU	1 RU
Dimensions	1.72H x 17.22W x 18.4D in (4.36 x 43.73 x 46.72 cm)	1.72H x 17.22W x 21.75D in (4.36 x 43.73 x 55.2 cm)
System Weight	12.75 lbs (5.7 kg)	19 lbs (8.62 kg)
Shipping Weight	28 lbs (12.70 kg)	30 lbs (13.61 kg)
Hardware specifications		
Network	2x10/100/1000	4x10/100/1000 plus Management and HA
Power	Fixed Power Supply	
Input Voltage	110-240V AC	110-240V AC
Rated Power	280W	300W
Power Supply[3]	48,000 hours	108,000 hours
Environmental		
Operating Temperature	0-40C	0-35C
Heat Output	950 BTU/hour typical	767 BTU/hour typical
Regulatory approvals		
Emissions	FCC, CCC, RoHS, WEEE, NOM, NYCE, V CCI, CE, UL, TUV, C-tick, AZ/NZS	CB, CE, UL, FCC, AZ/NZS, VCCI, C-Tick, GOST, KCCI, CCC, CSA, RoHS
Safety	UL 60950-1	UL 60950-1, CUL (CAN/CSA C22.2 No. 60950-1-03), CCC, CSA 60950-1-03, IEC 60950-1, EN 60950-1

1 Features listed here are applicable to AG 5.0 software or later

2 Features listed here are applicable to AG 8.1 software or later

3 MTBF calculated in accordance with Telcordia SR-332 “Parts Count” method

CITRIX®

Key Features

Security		
Encryption Methods	RSA, 3DES, AES	
Authentication Methods	LDAP RADIUS Active Directory Server-side digital certificates RSA SecurID and other RADIUS-based one-time password tokens Dual/stacked authentication	LDAP RADIUS Active Directory Server-side digital certificates Username/password Client-side digital certificates RSA SecurID and other RADIUS-based one-time password tokens Dual/stacked authentication
Directories	Active Directory LDAP RADIUS Dynamic Groups	Active Directory LDAP RADIUS Dynamic Groups Certificate Revocation Lists (CRL) Online Certificate Status Protocol (OCSP)
Password Management	Password change	
Access Control Options	Service/Port, URL, Host Name, Desktop (XenDesktop), Applications (XenApp), File Shares, Device Endpoint Scans	
Access and application support		
Browser-based Access	Yes	Yes
Mobile Access	Desktops (XenDesktop) and Applications (XenApp) for Windows Mobile, iPhone, iPad and Android	
Full Network Access	Provides access to any client/server or web application over a secure network tunnel for Windows and Mac clients	
Management and administration		
Centralized Management	Yes	Yes
Delegated Administration	No	Yes
High Availability		
High Availability	Yes	Yes

Citrix Access Gateway: Virtual Appliances

Security		
Model	AG VPX Express[4]	AG VPX
Max Concurrent Users	5	500
Physical host requirements (per VM)		
Hypervisor	Citrix XenServer 5.5 or later VMware vSphere ESX/ESXi 4.0 or later	
Processor	One or more Intel VTx or AMD-V 64-bit x86	
Memory	2 GB minimum	
Hard drive	40 GB	
Network interface	One 1 Gbps network adapter required (Recommended two 1 Gbps network adapters for two-arm deployments)	
Virtual machine requirements		
Virtual CPUs	One minimum, 2 or more recommended, 8 maximum	
Virtual Memory	1 GB minimum, 4GB maximum	
Virtual Disk	12 GB	
Virtual NICs	2	

4 VPX Express is a 12 month free trial license that includes 5 concurrent user licenses. Customers who require additional user licenses (up to 99) can request a 90-day EVAL license for AG VPX through a CSA Partner.

CITRIX®

Worldwide Headquarters
Citrix Systems, Inc.
851 West Cypress Creek Road
Fort Lauderdale, FL 33309, USA
T +1 800 393 1888
T +1 954 267 3000

www.citrix.com

Americas
Citrix Silicon Valley
4988 Great America Parkway
Santa Clara, CA 95054, USA
T +1 408 790 8000

Europe
Citrix Systems International GmbH
Rheinweg 9
8200 Schaffhausen, Switzerland
T +41 52 635 7700

Asia Pacific
Citrix Systems Hong Kong Ltd.
Suite 6301-10, 63rd Floor
One Island East
18 Westlands Road
Island East, Hong Kong, China
T +852 2100 5000

Citrix Online Division
6500 Hollister Avenue
Goleta, CA 93117, USA
T +1 805 690 6400

About Citrix
Citrix Systems, Inc. (NASDAQ:CTXS) is a leading provider of virtual computing solutions that help companies deliver IT as an on-demand service. Founded in 1989, Citrix combines virtualization, networking, and cloud computing technologies into a full portfolio of products that enable virtual workstyles for users and virtual datacenters for IT. More than 230,000 organizations worldwide rely on Citrix to help them build simpler and more cost-effective IT environments. Citrix partners with over 10,000 companies in more than 100 countries. Annual revenue in 2010 was $1.87 billion.

©2011 Citrix Systems, Inc. All rights reserved. Citrix® and Citrix Access Gateway™ are trademarks of Citrix Systems, Inc. and/or one or more of its subsidiaries, and may be registered in the United States Patent and Trademark Office and in other countries. All other trademarks and registered trademarks are property of their respective owners.

0411/PDF